



The **INDUSTRY'S**
EASIEST
to OPERATE
RATCHET LEVER HOIST

MODEL
LSB-B

McLaughlin Hoist & Crane
Authorized Sales & Service

(636) 343-9700

LSB-B Ratchet Lever Hoist

www.stlcrane.com

Coffing LSB-B Models are available with optional Load Limiters. Also featuring through-hardened load chain, these stamped steel ratchet lever hoists are lightweight, durable and are ideal for construction and commercial applications. All LSB-B hoists are metric rated.

CAPACITIES & LIFT - Rated loads of 3/4, 1 1/2, 3 and 6 tons, with 5, 10, 15 and 20 foot standard lifts. *Other lifts available.*

OPTIONAL LOAD LIMITER - Load Limiter alerts operator of a possible overload by allowing the handle to rotate without lifting the higher-than capacity load. The load limiter can be field-installed.

RUGGED AND LIGHTWEIGHT - Impact resistant, stamped steel housing withstands rigorous use. Compact design is portable and easy to rig.

LOW HANDLE EFFORT - Double reduction gearing and short, cushioned-grip handle provide easy operation with minimal handle effort.

360° ROTATING HANDLE - Provides versatile rigging options when used in confined spaces.

EASY FREE CHAINING - State-of-the-art free wheeling mechanism allows quick and easy one-handed take-up and positioning of slack chain.

POSITIVE LOAD CONTROL - Enclosed screw-and-disc type load brake stays clean and dry for positive load positioning. Latches on hooks provide positive load engagement.

OPTIONS - Shipyard hook available for 1 1/2 ton & 3 ton models

LIFETIME WARRANTY



3/4 - 6 Ton

● **SPECIFICATIONS** ●

LSB-B Ratchet Lever Hoists

Capacity		Model Number	Lift (ft.) *	Strands of Load Chain	Minimum Dist. Between Hooks (in.)	Handle Length (in.)	Average Handle Effort (lb.)	Net Weight (lb.)
(lb.)	(Ton)							
1500	3/4	LSB-1500B-5	5	1	11 5/8	9 1/4	46	12
1500	3/4	LSB-1500B-10	10	1	11 5/8	9 1/4	46	14
1500	3/4	LSB-1500B-15	15	1	11 5/8	9 1/4	46	16
1500	3/4	LSB-1500B-20	20	1	11 5/8	9 1/4	46	18
3000	1 1/2	LSB-3000B-5	5	1	13	14 9/16	59	21
3000	1 1/2	LSB-3000B-10	10	1	13	14 9/16	59	24
3000	1 1/2	LSB-3000B-15	15	1	13	14 9/16	59	27
3000	1 1/2	LSB-3000B-20	20	1	13	14 9/16	59	30
6000	3	LSB-6000B-5	5	1	16 5/16	14 9/16	75	35
6000	3	LSB-6000B-10	10	1	16 5/16	14 9/16	75	40
6000	3	LSB-6000B-15	15	1	16 5/16	14 9/16	75	45
6000	3	LSB-6000B-20	20	1	16 5/16	14 9/16	75	50
12000	6	LSB-12000B-5	5	2	22 3/4	14 9/16	76	67
12000	6	LSB-12000B-10	10	2	22 3/4	14 9/16	76	77
12000	6	LSB-12000B-15	15	2	22 3/4	14 9/16	76	88
12000	6	LSB-12000B-20	20	2	22 3/4	14 9/16	76	99

COFFING®
HOISTS

* Standard lifts shown. Other lifts available - Consult factory

Note: For complete dimensional data, refer to Coffing Dimensional Databook